# Steel Rotary Air Hydraulic Scissor Lift Table 24 In. x 48 In. 3,000 Lb. Capacity Blue

**MODEL AHLT-2448-3-43**

Ergonomic Solutions / Rotary Air/Hydraulic Scissor Lift Tables

## PRODUCT OVERVIEW

The rotary air/Hydraulic scissor lift table utilizes the convenience of factory air to power the lift table. Simply connect to an air supply through a filter, regulator, lubricator, and you will have a lift table suitable for a wide range of applications and operating environments. It features a pneumatic upper travel limit switch, safety toe guards, cylinder with internal safety velocity fuse, two button hand control, and life-time lubricated sleeve bearings.

## KEY FEATURES

- Utilizes the convenience of factory air for power
- Connect through a filter, regulator, or lubricator
- Suitable for a wide range of applications and environments
- Features a pneumatic upper travel limit switch and safety toe guards

## CORE PRODUCT DATA

| ASSEMBLED WEIGHT | ASSEMBLED SIZE | SHIP WEIGHT |
|---|---|---|
| 606 lbs | 24.375" W x 51" L x 7" H | 662 lbs |

| PACKAGE 1 SIZE | COLOR / FINISH | FREIGHT TYPE |
|---|---|---|
| 56" W x 36" D x 16" H | Blue | LTL Palletized |

**AVAILABILITY** Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 3,000 |
| **Platform Width/Length (in.)** | 24-3/8 x 48-3/8 |
| **Platform Raised Height (in.)** | 43 |
| **Platform Lowered Height (in.)** | 7 |
| **Minimum Supply (in.)** | 3/4 |
| **Air Inlet Size (in.)** | 1/2 |
| **Minimum (psi)** | 80 |
| **Minimum (cfm)** | 80 |
| **Control** | Handheld, 2 Button Pendant |
| **Pneumatic Toeguards OSHA Compliance** | 1910.212 |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?FID=197