

# Steel Knock-Down Adjustable Height Gantry Crane with Glass Filled Nylon Casters 15 Ft.Wide x 14 Ft. Max Usable Height 2,000 Lb. Capacity Blue

**MODEL AHSN-2-15-14**

Overhead Lifting / Adjustable Steel Gantry Cranes - Knockdown

## PRODUCT OVERVIEW

The industrial steel Gantry crane is designed for transporting and positioning materials along the beams length. The solid steel construction will provide years of service. Unit comes standard four (4) position locking swivel casters with roller bearings. Locks the rigging in 1 of 4 positions; you can set the wheels and push the gantry crane forward, back, left or right. There is an optional total locking casters that lock the rigging in any position and locks the wheel from rotating. More economical and flexible than permanent cranes and features a quick setup design. Painted blue finish with warning and operating stickers and complete owner's manual. Designed for semi-permanent or permanent applications. Requires assistance from fork truck to se...

## KEY FEATURES

- Heavy-duty welded steel construction for long lasting use
- Each unit includes four swivel glass filled nylon casters with four-way position locks for safe positioning
- Easily maneuvered between stations when unloaded
- All units comply with applicable CMAA and ANSI specifications

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**976 lbs**

**ASSEMBLED SIZE**  
**91.5" W x 179.75" L x 173.4375" H**

**SHIP WEIGHT**  
**932 lbs**

**PACKAGE 1 SIZE**  
**44" W x 102" D x 20" H**

**COLOR / FINISH**  
**Blue**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY** Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                      |                                     |
|--------------------------------------|-------------------------------------|
| Uniform Capacity (lb.)               | 2,000                               |
| Overall I-Beam Length (ft.)          | 15                                  |
| I-Beam Height (In.)                  | 6                                   |
| I-Beam Flange Width (in.)            | 4                                   |
| Under I-Beam Usable Height (in.)     | 102 to 168                          |
| Base Width (in.)                     | 91-1/2                              |
| Caster Quantity/Diameter/Width (in.) | (4) 8 x 2                           |
| Caster Style                         | Swivel (4) Position Locking Casters |
| Caster Material                      | Glass-Filled Nylon                  |
| Usable Travel Distance (in.)         | 149-3/4                             |
| Increment Height Adjustment (in.)    | 6                                   |
| Style                                | Knock-Down                          |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=518>