Aluminum Grip-Strut Walk Ramps with Handrails 143-3/4 In. x 39-3/8 In. 1900 Lb. Capacity Silver

MODEL AWR-G-38-12A-HR

Loading Dock Equipment / Aluminum Grip-Strut Walk Ramps

PRODUCT OVERVIEW

Load and unload trucks when docks are unavailable with the Aluminum grip-strut Walk Ramp with hand rails. The open deck design allows snow, ice and water to fall through ramp providing a positive grip for delivery men/women, shippers and receivers. One hundred (100) percent welded aluminum construction of the ramp and handrail is lightweight and will not rust. The brackets are constructed of powder coated steel for stability and durability. Overlap style end lip rests on the trailer bed to provide a smooth transition. Each unit includes two safety chains to connect the ramp to the trailer for safety. Not for pallet trucks or three wheel carts.

KEY FEATURES

- Welded aluminum ramp and handrail are light-weight and will not rust, held together by durable steel brackets for stability
- Overlap style end lip provides a smooth transition
- Safety chains securely connect ramp to trailer for safety
- Serrated ramp surface provides a non-slip grip

CORE PRODUCT DATA

ASSEMBLED WEIGHT	ASSEMBLED SIZE	SHIP WEIGHT
170 lbs	39.375" W x 143.75" L x 45.3125" H	170 lbs

PACKAGE 1 SIZE	COLOR / FINISH	FREIGHT TYPE
38" W x 144" D x 12" H	Silver	LTL Palletized

AVAILABILITY Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity with 4-wheel cart (lb.)	1,900
Uniform Capacity with 2-wheel cart (lb.)	1,400
Usable Width (in.)	36
Height Range (in.)	6 to 46
Safety Curbs (in.)	2
Usable Length (in.)	143-3/4
Deck Type	Grip-Strut
Usable Rail Length (in.)	122-5/16
Midrail (in.)	18-7/16
Railing Height (in.)	40-1/4
Installation	Bolt-on
Handrail Quantity	4

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **90 Days**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?FID=42