

# Steel Commercial Circulating Wall Fan 24 In. Black/Silver

**MODEL CCRF-24-W**

Facilities Maintenance / Commercial Circulator Fans



## PRODUCT OVERVIEW

The two speed, ball bearing, wall mount commercial circulating fan. Meets OSHA standards and is UL C/US listed. These portable blowers do not have a totally enclosed motor. They should be used in a clean and dry commercial application. The guard is coated steel with retaining clips. The fan has a steel hub and aluminum paddle blades.

## KEY FEATURES

- Meets OSHA standards and is UL C/US listed
- Pull chain switch for easy use
- SJT type 3 conductor cord
- Motor is permanently lubricated with split capacitor

## CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**43 lbs**

ASSEMBLED SIZE  
**12" W x 27" L x 27" H**

SHIP WEIGHT  
**43 lbs**

PACKAGE 1 SIZE  
**8" W x 29" D x 35" H**

COLOR / FINISH  
**Black / Silver**

FREIGHT TYPE  
**Parcel**

**AVAILABILITY** Quote Required - Please Contact Sales

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

**QUICKSHIP: --**

PRODUCT SPECIFICATIONS

|                             |                 |
|-----------------------------|-----------------|
| Blade Diameter (in.)        | 25              |
| Mounting Style              | Wall            |
| Amps High                   | 2.3             |
| CFM High                    | 5400            |
| CFM Low                     | 4300            |
| Electric Motor Horsepower   | 1/4             |
| Conductor Cord Length (in.) | 108             |
| Conductor Cord              | SJT type 3      |
| Voltage/Phase               | 115V/1PH        |
| CFM Medium                  | 4900            |
| OSHA                        | 1910.212 (a)(5) |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Gary, TN 37615

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA