# Vinyl Dock Seal 16 In. 8 Ft. x 8 Ft. Black

**MODEL D-150-16**

Loading Dock Equipment / Dock Seals

## PRODUCT OVERVIEW

The superior nylon reinforced vinyl facing has a higher tear strength than equivalent weight hypalon. The chemically sealed ends prevent moisture infiltration. It is mounted and bonded on a durable pressure treated wood and contains a full height air escape tunnel. The unit consists of a three (3) piece construction with beveled fronts and a through the wall installation kit that is included. Five inch (5") maximum compression is recommended. Application with a flush dock to building in conjunction with an Edge-O-Dock use a twenty (20) inch projection Dock Seal. To ensure proper size complete the survey sheet. This unit is non-returnable.

## KEY FEATURES

- Three foam-filled pads offer full dock protection
- Maximum compression design offers the maximum protection
- Built-in air tunnels allow air to escape when contacted by a trailer
- Mounting hardware and installation instructions make installation quick and easy

## CORE PRODUCT DATA

| ASSEMBLED WEIGHT | ASSEMBLED SIZE | SHIP WEIGHT |
|---|---|---|
| 128 lbs | 120" W x 16" L x 108" H | 221 lbs |

| PACKAGE 1 SIZE | COLOR / FINISH | FREIGHT TYPE |
|---|---|---|
| 36" W x 120" D x 22" H | Black | LTL Palletized |

**AVAILABILITY** Available

**QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Projection (in.)** | 16 |
| **Nylon Reinforced Vinyl (oz.)** | 36 |
| **Nylon Reinforced Guide Strips (in.)** | 2 |
| **Top Height (in.)** | 12 |
| **Side Wall Width (in.)** | 9-1/2 |
| **Face Width (in.)** | 12 |
| **Maximum Compression (in.)** | 5 |
| **Standard Guide Stipe Height (in.)** | 30 |
| **Side Height (in.)** | 96 |
| **Max Door Width (in.)** | 96 |
| **Max Door Height (in.)** | 96 |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **90 Days**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?FID=19