

Steel Floor Lock 4-3/8 to 5-1/4 In. Height Silver

MODEL FL-LKL-4

Facilities Maintenance / Polyurethane Floor Locks



PRODUCT OVERVIEW

Floor locks are ideal for maintenance and construction facilities. The unit is designed to create a stable environment, while decreasing the chance of jostling or slight movement. The unit is constructed of steel with a thermoplastic polyurethane base. To use, place the unit close to a desired wheel or caster and raise until tension is built. Once secured, a simple locking device can be activated by applying pressure to the foot pedal.

KEY FEATURES

- Steel construction for durability
- Thermoplastic polyurethane base for stability
- Locking device for quick service
- Lightweight for portability

CORE PRODUCT DATA

ASSEMBLED WEIGHT
2 lbs

ASSEMBLED SIZE
3.875" W x 4.375" L x 4.375" H

SHIP WEIGHT
2 lbs

PACKAGE 1 SIZE
5" W x 5" D x 5" H

COLOR / FINISH
Silver

FREIGHT TYPE
Parcel

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Lowered Height (in.)	4-3/8
Raised Height (in.)	5-1/4
Foot Pad Diameter (in.)	2-9/16
Foot Pad Material	Thermoplastic polyurethane (TPU)
Mounting Plate (in.)	3-7/8 x 3-9/16
Slotted Holes on Center (in.)	1-3/4 x 3-1/16
Mounting Plate Thickness (in.)	5/16
Slotted Mounting Hole Width/Height (in.)	3/8 x 1/2
Inside Bolt Hole Spacing (in.)	2-13/16 X 1-3/4
Outside Bolt Hole Spacing (in.)	3-1/16 X 1-3/4
Suggested Caster Size (in.)	4

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1067>