

# Stainless Steel Mezzanine Safety Double Wide Gate 79-5/16 In. x 108-1/2 In. x 80-1/16 In. Silver

**MODEL MEZZ-200-DW-SS**

Protective Barriers / Mezzanine Safety Gates

## PRODUCT OVERVIEW

The mezzanine safety gate provides an OSHA required handrail, mid-rail and kick plate for mezzanine without sacrificing load accessibility. To accommodate the maximum load height, when utilizing a standard pallet, load positioning within the gate is critical. For greatest amount of clearance and item placement flexibility, shorter loads are recommended. The gate rotates and design is balanced to allow for easy operation without use of springs.

## KEY FEATURES

- Access to mezzanines with safety first concept
- Manually operated gate rotates to allow access mezzanine
- Heavy-duty welded steel construction provides long lasting use
- Stainless steel offers an attractive appearance

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**209 lbs**

**ASSEMBLED SIZE**  
**108.5" W x 79.3125" L x 80.0625" H**

**SHIP WEIGHT**  
**284 lbs**

**PACKAGE 1 SIZE**  
**43" W x 102" D x 43" H**

**COLOR / FINISH**  
**Silver**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                                    |                           |
|----------------------------------------------------|---------------------------|
| Handrail Height (in.)                              | 42-3/8                    |
| Mid-Rail Height (in.)                              | 21                        |
| Kickplate Height (in.)                             | 4                         |
| Usable Width (in.)                                 | 96                        |
| Maximum Load Height (in.) / Utilizing pallet quant | 68 / (2) 48 x 48          |
| Attachment Method                                  | Lag Bolts                 |
| Compliance                                         | OSHA 29 CFR 1910.23 ( e ) |
| Tubing Size Square (in.)                           | 1-1/2 x 1-1/2             |
| Tube Thickness (in.)                               | .083                      |
| Overall Width (in.)                                | 108-1/2                   |
| Inside Width (in.)                                 | 98-1/2                    |
| Overall Height (in.)                               | 80-1/16                   |
| Inside Height (in.)                                | 78-3/8                    |
| Overall Length (in.)                               | 79-5/16                   |
| Inside Length (in.)                                | 76-11/16                  |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=645>