

Steel DC Powered Jib Crane 3-1/2 to 5-1/2 Ft. Boom 1,500 Lb. Capacity Blue

MODEL WTJ-E-15-3-DC

Overhead Lifting / Power Lift Jib Cranes



PRODUCT OVERVIEW

A power lift Jib crane is designed for material handling applications on docks, in warehouses or in truck beds. This lift jib crane is the economical answer to your material handling problems. It offers light-duty, intermittent use. Locking manual rotation. Unit is designed for vertical lifting only. Do not use unit for lifting personnel or overhead lifting.

KEY FEATURES

- Powered cable winch makes lifting and maneuvering easy
- Boom telescopes in and out for greater reach and versatility
- 360 Degrees swivel design allows for maximum accessibility
- Pre-drilled base plate makes mounting quick and easy

CORE PRODUCT DATA

ASSEMBLED WEIGHT
200 lbs

ASSEMBLED SIZE
13.5" W x 51.0625" L x 65.6875" H

SHIP WEIGHT
213 lbs

PACKAGE 1 SIZE
29" W x 65" D x 17" H

COLOR / FINISH
Blue

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	1,500
Boom Reach (in.)	43-1/16 to 66-3/4
Boom Height (in.)	47-1/8 to 73-5/16
Rotation Degree	360
DC (volts)	12
Horsepower	1
Wire Rope Length (ft.)	46
Wire Rope Diameter (in.)	3/16
Mounting Plate Length (in.)	12
Mounting Plate Width (in.)	12
1,500 lb. Capacity at Boom Extension (in.)	27-13/16
Capacity at 47-1/8" Fully Retracted (lbs.)	650
Capacity at 47-1/8" Mid-Position (lbs.)	300
Capacity at 47-1/8" Fully Extended (lbs.)	200
Capacity at 56-3/16" Fully Retracted (lbs.)	1100
Capacity at 56-3/16" Mid-Position (lbs.)	650
Capacity at 56-3/16" Fully Extended (lbs.)	550
Capacity at 64-3/4" Fully Retracted (lbs.)	1,250
Capacity at 64-3/4" Mid-Position (lbs.)	850
Capacity at 64-3/4" Fully Extended (lbs.)	650
Overall Width (in.)	13-1/2
Overall Retracted Length (in.)	51-1/16
Overall Height (in.)	65-11/16

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=582>